



# KEN

## PROFESSIONAL POWER TOOLS



Marketed & Serviced by :

# **Polymak**

*An Exceptional Power Tool Company*

**Polymak Tools (India) Pvt. Ltd.**

186/187, P.H.Road, Alsa Towers, Kilpauk, Chennai 600 010

Tel. 044-26401869 / 42857841

Fax: 044-42857654 E-mail: [info@polymak.co.in](mailto:info@polymak.co.in)

**9913B** 100mm (4") Angle Grinder



Double Insulation

**670W**

**SPECIFICATIONS**

|                     |           |
|---------------------|-----------|
| Max. Capacity (Dia) | 100mm     |
| No load speed       | 11000 rpm |
| Net Weight          | 1.5kg.    |

**9923** 100mm (4") Angle Grinder



Double Insulation

**860W**

**SPECIFICATIONS**

|                     |           |
|---------------------|-----------|
| Max. Capacity (Dia) | 100mm     |
| No load speed       | 11000 rpm |
| Net Weight          | 2.1kg.    |

**9925** 125mm (5") Angle Grinder



Double Insulation

**1240W**

**SPECIFICATIONS**

|                     |          |
|---------------------|----------|
| Max. Capacity (Dia) | 125mm    |
| No load speed       | 7500 rpm |
| Net Weight          | 3.1kg.   |

**9980** 180mm (7") Angle Grinder

**9230** 230mm (9") Angle Grinder



Double Insulation

**2450W**

**SPECIFICATIONS**

|                     | 9980     | 9230     |
|---------------------|----------|----------|
| Max. Capacity (Dia) | 180mm    | 230mm    |
| No load speed       | 8000 rpm | 6500 rpm |
| Net Weight          | 6.2kg.   | 6.2kg.   |

## 4100 110 mm Marble Cutter



 Double Insulation

**1200W**

### SPECIFICATIONS

|                      |            |
|----------------------|------------|
| Blade Dia meter      | 110mm      |
| Max.cutting capacity | 34mm       |
| No load speed        | 12000 rpm. |
| Net Weight           | 2.6kg.     |

## 7614N 355mm (14") Metal Cut-off Saw



**2300W**

### SPECIFICATIONS

|                      |              |
|----------------------|--------------|
| Wheel dia.           | 355mm        |
| Max.cutting capacity | at 90° 115mm |
| No load speed        | 3800 rpm.    |
| Net Weight           | 16.5kg.      |

## 2520E 20mm (3/4") Rotary Hammer



 Double Insulation

 Variable Speed

 Carrying Case

**500W**

### SPECIFICATIONS

|                  |            |
|------------------|------------|
| Dia. of bit      | 20mm       |
| No load speed    | 0-850 rpm. |
| Blows per minute | 0-3900/min |
| Net Weight       | 2.3kg.     |

## 2810 16mm Electric Breaker



 Double Insulation

 Carrying Case

**1050W**

### SPECIFICATIONS

|                  |          |
|------------------|----------|
| Dia. of bit      | 20mm     |
| Blows per minute | 2900/min |
| Net Weight       | 5.3kg.   |

## 9518BE 180mm Sander / Polisher



Double Insulation



Variable Speed



Electronic Speed Control

**1200W**

### SPECIFICATIONS

Max. capacities (Dia.)

Disc. dia 180mm

No load speed 0-600/3000 rpm.

Net Weight 3.2kg.

## 9100 110x100mm Finishing Sander



Double Insulation

**150W**

### SPECIFICATIONS

Capacities

Pad size 110mm x 100mm

Orbit per min 12000 opm.

Net Weight 1.3kg.

## 9025 6mm (1/4") Die Grinder



Double Insulation

**550W**

### SPECIFICATIONS

Collect Capacity 6mm

Wheel dia. 25mm

No load speed 23500 rpm.

Net Weight 2.2kg.

## 9725 125mm Straight Grinder

## 9750 150mm Straight Grinder



Double Insulation

**950W**

### SPECIFICATIONS

|               | 9725      | 9750      |
|---------------|-----------|-----------|
| Wheel dia.    | 125mm     | 150mm     |
| No load speed | 5000 rpm. | 5000 rpm. |
| Net Weight    | 3.2kg.    | 4.8kg.    |

## 6114ER Cordless Driver Drill



-  Double Insulation
-  Variable Speed
-  Reversing
-  Electric Brake
-  Torque Setting 15
-  2 Extra Batteries
-  Carrying Case

14.4V Ni-Cad  
6114ER

## SPECIFICATIONS

|               |            |
|---------------|------------|
| Capacity      |            |
| Wood          | 38mm       |
| Steel         | 13mm       |
| Aluminum      | 15mm       |
| Screw         | 8mm        |
| No load speed | 0-700 rpm. |
| Max. Torque   | 28 N.m     |
| Net Weight    | 1.7kg      |

## 6713ED Impact Drill 13mm



-  Double Insulation
-  Variable Speed
-  Carrying Case

650W

## SPECIFICATIONS

|               |             |
|---------------|-------------|
| Dia. of bit   | 13mm        |
| No load speed | 0-2600 rpm. |
| Net Weight    | 3.5kg.      |

## 6310ER 10mm High Speed Drill



-  Double Insulation
-  Variable Speed
-  Reversing

680W

## SPECIFICATIONS

|               |             |
|---------------|-------------|
| Dia. of bit   | 10mm        |
| No load speed | 0-3000 rpm. |
| Net Weight    | 1.8kg.      |

## 6816NB 16mm Drill



-  Carrying Case

1200W

## SPECIFICATIONS

|               |          |
|---------------|----------|
| Dia. of bit   | 16mm     |
| No load speed | 550 rpm. |
| Net Weight    | 4.5kg    |

## 1160E Jig Saw



Double Insulation



Bayonet Shank Jig Saw Blade



Orbital Cutting



Variable Speed



Electronic Speed Control



Carrying Case



**500W**

### SPECIFICATIONS

Max. Cutting Capacity

In wood at 90° 55mm

In Steel at 90° 10mm

Strokes per minute 500-3000

Net Weight 2.3kg.

## 1982N 82mm Power Planer



Carrying Case



**600W**

### SPECIFICATIONS

Planing width 82mm

Cuttin Depth 2mm

No load speed 15000 rpm.

Net Weight 4.0kg.

## 3912B 12mm Electric Router



Double Insulation



**1850W**

### SPECIFICATIONS

Capacity 12mm

No load speed 23000 rpm.

Net Weight 6.6kg.

## 7210 255mm Compound Miter Saw



Double Insulation



Electric Brake



Bevel Cutting (45° Left)



Dust Collecting



**1650W**

### SPECIFICATIONS

Blade Dia meter 255mm

Max.cutting capacity

at 90° 93x95mm

at 45° 93x67mm

No load speed 5000 rpm.

Net Weight 11kg.

**5627N 180mm Circular Saw**



**SPECIFICATIONS**

|                    |        |            |
|--------------------|--------|------------|
| Cutting Capacities | at 90° | 58mm       |
|                    | at 45° | 40mm       |
| Blade Dia          |        | 180mm      |
| Speed              |        | 5000/min.. |
| Net Weight         |        | 5.0kg.     |

**5216N 16" Electric Chain Saw**



**SPECIFICATIONS**

|                    |             |
|--------------------|-------------|
| Standard Guide bar | 405mm (16") |
| Chchain Pitch      | 3/8"        |
| Gauge              | 0.050"      |
| Chain speed        | 400m/min..  |
| Net Weight         | 6.0kg.      |

**Nearest Authorised Channel Partner:**



PROFESSIONAL POWER TOOLS

